

COLOR	MINIMUM LUMINOUS FLUX (lm) OR RADIOMETRIC POWER (mW)	TYPICAL EFFICACY (lm/W) OR RADIANT EFFICACY (%)	TEST CURRENT	TEST JUNCTION
Deep Red	260	37%	350	25°C
	300	41%	350	25°C
	350	46%	350	25°C
Red	30	37	350	25°C
	40	65	350	25°C
	40	47	350	25°C
	50	75	350	25°C
	50	53	350	25°C
	50	73	350	25°C
	60	83	350	25°C
	60	87	350	25°C
	70	98	350	25°C
Red-Orange	80	112	350	25°C
	50	57	350	25°C
	50	72	350	25°C
	60	91	350	25°C
	60	63	350	25°C
	60	84	350	25°C
	70	98	350	25°C
	70	101	350	25°C
PC Amber	80	112	350	25°C
	90	80	350	25°C
	100	89	350	25°C
	110	96	350	25°C
Amber	105	105	350	25°C
	30	37	350	25°C
	40	46	350	25°C
	50	51	350	25°C
	50	71	350	25°C
	60	60	350	25°C
	60	87	350	25°C
	70	98	350	25°C
Lime	80	113	350	25°C
	140	154	350	85°C
	150	163	350	85°C
	160	174	350	85°C
	170	181	350	85°C
	180	190	350	85°C
Green	190	201	350	85°C
	70	78	350	25°C
	80	86	350	25°C
	90	93	350	25°C
Cyan	100	100	350	25°C
	60	66	350	25°C
	70	75	350	25°C
Blue	80	81	350	25°C
	18	21	700	25°C
	24	26	700	25°C
	30	33	700	25°C
Royal Blue	40	38	700	25°C
	500	48%	700	25°C